Data Sheet DHB-E 13 SLi 60°C



Instantaneous 3 Phase Electric Water Heater

Instant hot water up to 60°Celsius



The advantages

-) Made in Germany
- > Rotary dial temperature selection from 30-60° Celsius
-) Bare wire element for fast and efficient water heating
- > Suitable for hard and soft water areas
- > No flue, ventilation or safe tray required
- Electronically controlled to accurately regulate the water temperature output
- > Electronic safety system with air detection
- > Compact design for space saving installation flexibility
- > Multiple electrical access points for installation ease
- > Available in electrical size:
- > DHB-E13 SLi 14.6kW, 20 Amps per phase, 3 phase 415V
- > WaterMark approved licence number WMKA00301, AS3498









Ideal installation areas*

- **)** Bathrooms
- Apartments
- > Factory bathrooms or sinks
- Xitchenettes
- > Restaurants or Cafes

For more information on the right Stiebel Eltron water heater for your project please contact our Technical Services Department on free call 1800 153 351 (Australia).

^{*}Dependent on model selected

Data Sheet DHB-E 13 SLi 60°C



Instantaneous 3 Phase Electric Water Heater

Instant hot water up to 60°Celsius

Selecting the right Stiebel Eltron instantaneous water heater Thank you for considering the Stiebel Eltron instantaneous water

heater, with over 90 years of hot water technology experience we are sure you will be happy with your choice of a Stiebel Eltron instantaneous water heater.

The temperature rise table will assist you in determining the appropriate size of instantaneous water heater required for your application. The required temperatures at specific flow rates will determine the size of system needed. Our customer support representatives can be contacted on our free call number 1800 153 351 to assist in selecting the appropriate system/systems for your project.

Installation close to the point of use

The Stiebel Eltron DHB-E13 instant water heaters compact design allows for ease of installation close to the point of use. In order to minimise thermal losses in the pipe work the water heater should be installed as close to the point of use as possible.

Electrical installation

This water heater must be installed in accordance with AS/NZS3000 electrical regulations by a qualified installer.

Plumbing installation

This water heater must be installed in accordance with AS/NZS3500.4.2 and local authority regulations by a qualified installer.

Warranty

For full warranty information please visit www.stiebel.com.au.

Technical Support


Stiebel Eltron (Aust) Pty Ltd Free Call: 1800 153 351

Telephone (Australia): (03) 9645 1833

Website: stiebel.com.au

	3 PHASE ELECTRIC
Model number	DHB-E 13 SLi 60°C
Power output	14.6kW
Rated voltage	415 V
Rated current	20 Amp
Phases	3/PE
Electrical installation	As per AS/NZS3000
Installation requirements	AS/NZS3500.4.2 & local requirements
Switch on flow rate	3.0 L/min
Permissible operating pressure	1000 kPa
Temperature adjustment	30°C-60°C
IP Rating	IP25 (IP24 power supply for finished walls)
Height	478 mm
Width	225 mm
Depth	105 mm
Weight (filled with water)	5.5 kg
Colour	white
Nominal capacity	0.4L
Approvals	WaterMark Lic No. WMKA00301. AS3498
Equipment	
For one/several draw off points	Yes / Yes
Heating system	Bare wire
Electronic flow rate control	<u>-</u>
Electronic air detection system	<u>-</u>
Accepts pre-heated water (solar)	<u>-</u>
Programmable temperature	<u>-</u>
Wellness shower programs	-
ECO energy & water function	<u>-</u>
Optional accessories	
Radio remote control primary	<u>-</u>
Radio remote control secondary	-

DHB-E13 SLi 60°C instantaneous 3 phase electric water heater



STIEBEL ELTRON is committed to our policy of continual improvement, some features may have subsequently been changed or even removed. Our advisors will be happy to consult with you regarding the currently applicable equipment features. The images used in this brochure are for reference only.