

STIEBEL ELTRON

VLR 70 S

VLR 70 L

Decentralised heat recovery
ventilation unit installed
in pairs to create a healthy
indoor environment



VLR 70 S / VLR 70 L

HEAT RECOVERY VENTILATION

Decentralised ventilation with heat recovery


Create a pleasant indoor environment in the home with the VLR 70 decentralised heat recovery ventilation units. Installed in pairs with ducting through the walls, the VLR 70 has a heat recovery level of up to 92%.



Product features

- › Up to 92% heat recovery
- › Decentralised ventilation- easy installation for new or existing buildings
- › Supplies fresh air from outside into your home or office
- › Prevents the growth of mould with improved air ventilation
- › Hygienic aluminium heat exchanger
- › Quiet operation
- › Installed in pairs, connect up to 8 units together

Dimensions



		VLR 70 L Trend	VLR 70 S Trend
A	mm	80	200
B	mm	300-550	100-300

Type		VLR 70 S Trend	VLR 70 L Trend
Article no.		200002	201458
Air flow rate	m ³ /h	10 - 70	10 - 70
Heat recovery level		Up to 92 %	Up to 92 %
Filter class		F7 / G2	F7 / G2
Max. power consumption (8 units)	W	92	92
Connection		1/N 100-240 V 50/60 Hz	1/N 100-240 V 50/60 Hz
Max. current (8 units)	A	3.8	3.8
Sound power level at 20 m ³ /h	dB(A)	35	35
IP rating		IP 21	IP 21
Maximum altitude for installation	m	2000	2000
Operating temperature range	°C	-14 to +40	-14 to +40
Wall thickness	mm	100 - 300	300 - 550
Min. outlet aperture	mm	Ø200 square 185 x 185	Ø200 square 185 x 185
Height	mm	285	285
Width	mm	360	360
Depth	mm	590	780
Weight	kg	5.2	5.2

STIEBEL ELTRON is committed to our policy of continual improvement, some features may have subsequently been changed or even removed. Our advisors will be happy to consult with you regarding the currently applicable equipment features. The images used in this data sheet are for reference only.