

STIEBEL ELTRON

RTF
Connect



RTF Connect

UNDERTILE HEATING CONTROLLER

STIEBEL ELTRON's RTF-Connect makes it easier than ever to use and control your under-tile heating. With a hassle-free setup, you can have full control at the thermostat or via the app. The app provides complete control over heating zones, individual thermostats, heating schedules, and heating modes.

Product features

- › WiFi connectivity
- › Trouble-free setup and use
- › No gateway required
- › APP-name SWATT in APP-store
- › Redundant control - full control at the thermostat
- › Full APP-control of heating zones, individual thermostats, heating schedules, heating modes



Download the app



	205775
Model	RTF-Connect
Dimensions with frame	115mm x 84mm
Depth	40mm
Built in depth	22mm
Weight	.22kg
Colour	White
Method of mounting	Wall mounting in a socket or mounting box
Supply voltage	100-240VAC +/-10% 50/60Hz
Max. pre fuse	16 A
Enclosure rating	IP 21
Output load	Max. 16A / 3600 W
Standby consumption	<= 0.5 W
Security	WPA/WPA2
Display	176 x 220 pixels TFT-resistive touch
RTF-frequency band	2.4 GHz
WIFI	IEEE 802.11 b/g/n - 2.4GHz

STIEBEL ELTRON is committed to our policy of continual improvement, some features may have subsequently been changed or even removed. Our advisors will be happy to consult with you regarding the currently applicable equipment features. The images used in this data sheet are for reference only.