















## QLD Product Selection Guide

### Water heating




Below table helps you to identify the right STIEBEL unit depending on the number of fixture outlets that you wish to serve. Be aware that the table serves as general guidance only. If you require further assistance, please free call our national service centre on 1800 153 351.

Please select 1 column





Water Heater Model		Ideal Installation	Electrical Loading	Flow Rate & Temperature Rise	H × W × D (mm)								
3-PHASE ELECTRIC INSTANTANEOUS	 DHE 27 AU	<ul style="list-style-type: none"> <li>› Kitchen sink (60°C)</li> <li>› Bathroom (suitable for use with a TMV)</li> <li>› Commercial glass or dish washing</li> </ul>	28.0 kW 40 Amps per Phase 3 Phase 415 V	Internally electronically controlled. Automatically adjusts flow to deliver right temperature.	466 × 225 × 116	3	2	3	4				
	DHE 18 AU	<ul style="list-style-type: none"> <li>› Can accept pre-heated hot water of up to 55°C</li> </ul>	19.4 kW 27 Amps per Phase 3 Phase 415 V							2	2	2	3
	 DEL 27 PLUS	<ul style="list-style-type: none"> <li>› Delivers a maximum water temperature of 50°C (AS3498)</li> </ul>	28 kW 39 Amps per Phase 3 Phase 415 V	18 L/min = 22°C rise (= 2 showers mixed)	466 × 225 × 116	2	2	3	4				
	DEL 18 PLUS	<ul style="list-style-type: none"> <li>› Kitchen sink (50°C)</li> <li>› Bathroom</li> </ul>	19.4 kW 27 Amps per Phase 3 Phase 415 V	15 L/min = 19°C rise (= 1 shower, 1 basin, mixed)						2	2	3	3
	DEL 13 PLUS	<ul style="list-style-type: none"> <li>› Eco-Mode - Electronically adjust the flow rate</li> </ul>	14.5 kW 20 Amps per Phase 3 Phase 415 V	12 L/min = 17°C rise (= 1 shower, 1 basin, mixed)						1	1	1	2
	SINGLE PHASE	 DHB-E 27 LCD	<ul style="list-style-type: none"> <li>› Kitchen sink (60°C)</li> <li>› Bathroom (suitable for use with a TMV)</li> <li>› Commercial glass or dish washing</li> </ul>	28 kW 39 Amps per Phase 3 Phase 415 V	18 L/min = 22°C rise (= 2 showers mixed)	466 × 225 × 116	3	2	3	4			
DHB-E 18 LCD		19.4 kW 27 Amps per Phase 3 Phase 415 V		15 L/min = 19°C rise (= 1 shower, 1 basin, mixed)	2						2	2	3
DHB-E 13 LCD		14.5 kW 20 Amps per Phase 3 Phase 415 V		12 L/min = 17°C rise (= 1 shower, 1 basin, mixed)	1						1	1	2
 DHCE 8/60		<ul style="list-style-type: none"> <li>› Bathroom (suitable for use with a TMV)</li> <li>› 2 Basins</li> <li>› 1 Sink</li> </ul>	9.5 kW 40 Amps Single phase 240 V (hard wired)	6 L/min = 23°C rise	360 × 200 × 110	1	0	1	2				
 DHCE 8/50		<ul style="list-style-type: none"> <li>› Delivers a maximum water temperature of 50°C (AS3498)</li> </ul>	9.5 kW 40 Amps Single phase 240 V (hard wired)	6 L/min = 23°C rise						1	0	1	2
 DHCE 6/50		<ul style="list-style-type: none"> <li>› 2 Basins</li> <li>› 1 Sink</li> </ul>	7.1 kW 30 Amps Single phase 240 V (hard wired)	6 L/min = 17°C rise						0	0	0	2
 DEM 6	<ul style="list-style-type: none"> <li>› 1 Basin</li> </ul>	6.2 kW 25 Amps Single phase 240 V (hard wired)	4 L/min = 22°C rise	143 × 190 × 82	0	0	0	1					

Water Heater Model		Ideal Installation	Electrical Loading	Storage Capacity	H × W × D (mm)
COMPACT STORAGE	 SNU 10 Plus SNU 5 Plus	<ul style="list-style-type: none"> <li>› 1 kitchen sink</li> <li>› Stores water up to 85°C</li> <li>› Must be fitted with STIEBEL's open vented tapware</li> <li>› Coloured tapware now available</li> </ul>	2 kW 8.3 Amps Single phase 240 V (plug in)	10 litres 5 litres	503 × 290 × 282 423 × 240 × 212
	 SHC 15 AU SHC 10 AU	<ul style="list-style-type: none"> <li>› Kitchen sink (60°C)</li> <li>› Can be used with any tapware</li> <li>› Suitable for more than 1 fixture outlet</li> </ul>	1.6 kW 10 Amps Single phase 240 V (plug in)	15 litres 10 litres	523 × 320 × 318 498 × 280 × 270
	 HOT 2.6 N Premium	<ul style="list-style-type: none"> <li>› 1 kitchen sink</li> <li>› Residential approved</li> <li>› Temp between 15°C-95°C</li> <li>› 70 cups per hour</li> <li>› Must be fitted with Stiebel Mono or 3in1 tap</li> </ul>	1.6 kW 7.3 Amps Single phase 240 V (plug in)	2.6 litres	450 × 200 × 145

#### Legend & Assumptions

-  shower(s)
-  sink(s)
-  basin(s)

Cold Water Temperature = 15°C  
Mixed Water Temperature, delivered at outlet = 40°C  
Shower Rise Flowrate 9 L/min  
Sink Flowrate 7.5 L/min  
Basin Flowrate 6 L/min

Water Heater Model		Ideal Installation	Electrical Loading	Storage Capacity	H × W × D (mm)
HEAT PUMP	 WWK 222/222H	<ul style="list-style-type: none"> <li>› House</li> <li>› Suitable for 2-3 people household</li> </ul>	0.55 kW 10 Amps Single phase 240 V	220 litres	∅ 690 1553-1569 (adjustable feet)
	 WWK 302/302H	<ul style="list-style-type: none"> <li>› House</li> <li>› Suitable for 4-6 people household</li> </ul>	0.55 kW 10 Amps Single phase 240 V	302 litres	∅ 690 1921-1937 (adjustable feet)
	 SHP-O 200 Plus	<ul style="list-style-type: none"> <li>› House</li> <li>› Suitable for 2-3 people household</li> </ul>	0.45 kW, Single phase 240V (AS/NZS 5125.1)	200 litres	∅ 650 1478
	 SHP-O 300 Plus	<ul style="list-style-type: none"> <li>› House</li> <li>› Suitable for 4-6 people household</li> </ul>	0.44 kW, Single phase 240V (AS/NZS 5125.1)	300 litres	∅ 650 1903

## QLD Product Selection Guide


### Water heating

Instantaneous water heaters by STIEBEL ELTRON use electricity to produce hot water. The power needed depends on the cold water inlet temperature as well as the desired water flow rate: a low cold water temperature combined with high flow rates require a more powerful appliance to heat water.

### Cold water inlet temperature in QLD approx. average of 18°C

The below chart shows the temperature rises that can be achieved by an electric instantaneous water heater based on its kW rating. To determine an approximate outlet temperature, add the below figure to the cold water temperature of your area.

EXAMPLE: A DHE 18 AU with a rated output of 19.4 kW comes with a temperature rise of approximately 40 °C at a flow rate of 7 L/min. Add 40 °C to a cold water temperature of 18 °C in Brisbane, and you get an approximate outlet temperature of 58 °C.



For the most up to date product information, diagrams and data sheets, head to [stiebel-eltron.com.au/downloads](http://stiebel-eltron.com.au/downloads)

### Temperature Rise Chart

Cold water temperature + temperature rise at certain flow rate = outlet temperature.  
Please note that the maximum outlet temperature of each model will never be exceeded.

Model	Rated Output	Flow Rate in L/min													
		1.5	2.5	3	4	4.5	5	6	7	8	9	10	11	12	13
DHE 18 AU	19.4 kW		60 °C	60 °C	60 °C	60 °C	55 °C	45 °C	40 °C	35 °C	31 °C	28 °C	25 °C	23 °C	21 °C
DHE 27 AU	28.0 kW		60 °C	60 °C	60 °C	60 °C	60 °C	60 °C	59 °C	52 °C	46 °C	42 °C	38 °C	35 °C	32 °C
DEL 13 PLUS	14.5 kW			50 °C	50 °C	46 °C	41 °C	35 °C	30 °C	26 °C	23 °C	21 °C	19 °C	17 °C	
DEL 18 PLUS	19.4 kW		50 °C	50 °C	50 °C	50 °C	50 °C	46 °C	40 °C	35 °C	31 °C	28 °C	25 °C	23 °C	21 °C
DEL 27 PLUS	28.0 kW		50 °C	50 °C	50 °C	50 °C	50 °C	50 °C	50 °C	50 °C	44 °C	40 °C	36 °C	33 °C	31 °C
DHB-E 13 LCD	14.5 kW			60 °C	52 °C	46 °C	41 °C	35 °C	30 °C	26 °C	23 °C	21 °C	19 °C	17 °C	
DHB-E 18 LCD	19.4 kW			60 °C	60 °C	60 °C	55 °C	45 °C	40 °C	35 °C	31 °C	28 °C	25 °C	23 °C	21 °C
DHB-E 27 LCD	28.0 kW			60 °C	60 °C	60 °C	60 °C	60 °C	57 °C	50 °C	44 °C	40 °C	36 °C	33 °C	31 °C
DEM 6	6.2 kW		35 °C	30 °C	22 °C	20 °C	18 °C								
DHCE 6/50	7.1 kW	50 °C	41 °C	34 °C	26 °C	23 °C	20 °C	17 °C	15 °C	13 °C	11 °C				
DHCE 8/50	9.5 kW	50 °C	50 °C	45 °C	34 °C	30 °C	27 °C	23 °C	19 °C	17 °C	15 °C				
DHCE 8/60	9.5 kW	60 °C	54 °C	45 °C	34 °C	30 °C	27 °C	23 °C	19 °C	17 °C	15 °C				

\*This is intended as a guide only. Installation, pipework and voltages can cause discrepancies.



Have we sparked your interest? For further information visit [www.stiebel.com.au](http://www.stiebel.com.au) or call our service team on 1800 153 351.